



RECOMMENDED MOUNTING HOLE DIMENSIONS (inches)



1. MAX. PANEL THICKNESS=0.185"

MileTek[®] MilesTek Corporation
 1506 Interstate 35 West
 Denton, Tx 76207

Telephone: 940.484.9400 • Toll Free: 866.524.1553
 Fax: 940.591.7086 • Web: www.milestek1553.com

PART NUMBER: 10-06567	CAGE CODE: 4Z977
TITLE: TRB NON-ISOLATED BULKHEAD JACK TO JACK FEEDTHRU	
UNIT: mm	DATE: 08/2/2005
REV:	SHEET: 1/1

APPROVED	MARK HEARN
CHECKED	ROBERT PEREZ
ISO 9001: 2000 CERTIFIED	

UNLESS OTHERWISE SPECIFIED TOLERANCES:
 0.5-5 = ±0.2
 5-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1

NO	DESCRIPTION	MATERIAL
1	CONTACT BODY	BRASS/GOLD PLATE
2	INSULATOR	TEFLON
3	CONTACT PIN	BERYLLIUM COPPER GOLD PLATE 30 μ"
4	LOCK RING	BRASS/NICKLE PLATE
5	INSULATOR	TEFLON
6	BODY	BRASS/NICKLE PLATE
7	LOCK RING	BRASS/NICKLE PLATE
8	GASKET	RUBBER/ORANGE
9	WASHER	SS41/NICKEL PLATE
10	NUT	BRASS/NICKEL PLATE